

# Managing Groundwater Storage - Managed Aquifer Recharge in California

American Geosciences Institute Webinar

July 18, 2018

Timothy K. Parker, PG, CEG, CHG  
Parker Groundwater, Sacramento CA

[tim@pg-tim.com](mailto:tim@pg-tim.com) 916-833-5800

# California's 2014 Sustainable Groundwater Management Act

## Requires

- Formation of Groundwater Sustainability Agencies in High and Medium Priority Basins by June 2017
- Development of Groundwater Sustainability Plans by January 2020 Critically Overdrafted Basins and January 2022 Others
- Become Sustainable within 20 years of GSP Adoption
- State may intervene if these mandates not met by locals


## Perfect Hydrologic Storm

- Five years of drought
- Less surface water being delivered by state and federal systems due to drought and environmental constraints
- More groundwater being pumped due to above
- Increasing land subsidence
- Impacts to water conveyance
- Disadvantaged communities nitrate impacted groundwater

# California SGMA and COD Basins

## SGMA Basins are High and Medium Priority

## Critically Overdrafted Basins




# California's 2014 Sustainable Groundwater Management Act

## Requires

- Formation of Groundwater Sustainability Agencies in High and Medium Priority Basins by June 2017
- Development of Groundwater Sustainability Plans by January 2020 Critically Overdrafted Basins and January 2022 Others
- Become Sustainable within 20 years of GSP Adoption
- State may intervene if these conditions not met

## Status



***Sustainability = increase supply, recharge or reduce demand***

# California Statewide Challenges

- 100's to 1,000's of recharge projects are needed statewide to stabilize groundwater declines and need for incentives to do so
- Determine the most suitable soil, geologic setting and aquifer space for recharge, and what rates can be achieved
- Need to know where, how much and how frequently surface water will be available for recharge, considering instream (environmental) flow needs and climate change
- Changes in reservoir reoperation and additional conveyance needed to maximize and optimize recharge opportunities
- Determine potential benefits and possible adverse impacts of increasing recharge to water quality based on different land and water management strategies and how compatible the existing regulatory system will be
- Regulatory permitting and legal water rights uncertainties need to be addressed with an emphasis of the public benefits of recharge and sustainability

***Increasing Groundwater Recharge through Changing Management Practices is a Recognized Part of the Solution***

# Managing Groundwater Storage = Managed Aquifer Recharge (MAR)

- The purposeful recharge of an aquifer under controlled conditions to store the water for later extraction or to achieve environmental benefits.
- Requires:
  - Source of Water
  - Conveyance
  - Suitable receiving aquifer
  - Water rights
  - Satisfy regulations

# WHY MAR?

- A tool to replenish aquifers and provide water supply security
- Generally the cheapest form of new water supply available
- Can be used to replenish depleted aquifers, protect and enhance groundwater-dependent ecosystems, and avoid saline intrusion and land subsidence
- Can help offset the costs of flood control and water reuse in urban areas where demand is out of balance with supply

# Advantages & Challenges for MAR Compared to Surface Reservoirs

## MAR Advantages

- Smaller impact on land use
- Protection against evaporative losses and algae bloom, fall out
- High natural attenuation
- Dampens quality and temperature
- Lower cost
- Can be scaled up over time to spread out capital investment

## MAR Challenges

- Need suitable aquifer system
- Aquifers not water tight - losses
- Surrounding saline water may mix
- Reactions of source water with groundwater and aquifer matrix
- Infiltration/recovery rates can be limited by clogging
- Potentially higher operations and maintenance

# Managing Groundwater Storage - Managed Aquifer Recharge

## ***A Proven and Well Demonstrated Technology***

- Economics good and typically costs less than alternative water sources, and staged implementation affordable
- Can be implemented as mutually beneficial projects for environmental and water quality improvements along with supply resiliency and security
- Adaptable to different settings, opportunities and constraints including fresh, brackish or saline receiving aquifers, using drinking water, recycled water, stormwater or groundwater as the source water

# Most Common Types of MAR

## ***MAR Type and Design Governed by Hydrogeologic Setting and Hydrology***

- Infiltration Basins
- Aquifer Storage & Recovery Wells (ASR)
- Aquifer Storage, Treatment & Recovery (ASTR)
- Dry Wells
- Bank Filtration
- Sand or Check Dams
- Distributed Projects
  - Flood MAR
  - Low Impact Development


# Design Considerations

- Detailed hydrogeologic characterization
- Source and receiving water characterization
  - Source -Turbidity, pH, Total Organic Carbon, Metals
  - Receiving – Redox, Dissolved Oxygen, Salinity, Metals (Fe, Al, Mn), Red
- Clogging – very important because it will happen
  - Can be physical, chemical, mechanical, biological
  - Manage through engineering design, chemical intervention, performance monitoring and operational practices
  - Treatment options include strainers, filtration (sand and filters), microfiltration, disinfection, chemicals

# MAR Facilities

## Santa Clara Valley

### Water District



- Instream Recharge
- District Recharge Ponds or Facilities
- Santa Clara Subbasin (DWR Basin 2-9.02)
- Llagas Subbasin (DWR Basin 3-3.01)
- Santa Clara Plain Confined Area
- Santa Clara Plain Recharge Area
- Coyote Valley Recharge Area
- Llagas Subbasin Confined Area
- Llagas Subbasin Recharge Area
- Approximate Extent of Confined Area
- Reservoir
- Salt Ponds
- Santa Clara County

# MAR Facilities

## Santa Clara Valley

### Water District





Diablo  
Range

- Land subsidence about 13 feet in San Jose between 1915-1970
- 393 acres of recharge ponds
- 91 miles of controlled in-stream recharge
- Recharge approximately 100,00 acre-feet per year




# Regional Water Authority Sacramento Groundwater Authority






- Water Forum Agreement signed after 8 years of facilitated discussions
- Formed Regional Water Authority and Sacramento Groundwater Authority 1998
- Set in-streams flow for American River to avoid fisheries impacts
- Implemented a conjunctive use program cross connecting water distributions systems
- Successfully stored nearly 150,000 acre-feet of water in- lieu of pumping
- Water Accounting Framework in place for future potential exports



# Kern Water Bank Participants



Dudley Ridge  
WD

KINGS

TULARE

KERN

Westside Mutual  
Water Company

Semitropic  
WSD

Plant - Kern Canal

Kern River

California Aqueduct

KWB


KCWA  
ID4

Wheeler Ridge-Maricopa WSD

SANTA BARBARA

KERN  
VENTURA

Tejon-Castac  
WD





## Kern Water Bank

- Started operating in 1994
- Multi-benefit project for ecosystems – one of the top freshwater wetlands in state
- 70 shallow recharge ponds covering 7,000 acres situated on coarse grained Kern River alluvial fan deposits
- Average recharge rate about 1/3 foot per day
- Maximum annual recharge capacity about 500,000 acre-feet per year
- 84 recovery wells - average depth about 750 feet below ground surface
- Annual recovery capacity about 240,000 acre-feet at recovery program beginning




# MAR Facilities



WATER  
REPLENISHMENT  
DISTRICT OF  
SOUTHERN CALIFORNIA

**WRD**  
4040 Paramount Blvd  
Lakewood, CA 90712  
(562) 921-5521  
(562) 921-6101 (fax)  
www.wrd.org





0 2.5 5 10  
Kilometers

0 2.5 5 10  
Miles



- Seawater intrusion was the catalyst in the 30's and 40's
- LA County started installing injection wells along coast in 1950's
- WRD formed in 1959 to recharge groundwater
- Adjudications:
  - 1961 West Coast basin
  - 1965 Central basin
- Capped pumping above safe yield at 281,835 AFY
- WRD provides replenishment to meet safe yield annually
- Projects 2018 recharge 70,000 AF by spreading in basins and 30,000 AF by injection
- Use stormwater, recycled water and imported water
- Moving away from unreliable imported water






# MAR Facilities Orange County Water District

Over 1,000 acres of spreading facilities





- Recharge Facility
- City Of Anaheim Pipeline
- Groundwater Replenishment System Pipeline
- Inflatable Rubber Dam
- Recharge Water Pipeline
- Transfer Tube



DISCLAIMER: This map is provided only as a convenience to the user to provide general information. The Orange County Water District does not regularly update this map or the information contained on it, and is provided in an "as-is" condition for you to view, access, copy, distribute and otherwise use at your own risk. The map and the information contained on it should be considered out of date and they should not be relied upon for any legal, engineering, surveying or similar purposes. Orange County Water District makes no representation or warranty of any kind, whether express or implied, regarding the map or any of the information contained on it. By accessing the map, you release the Orange County Water District from any liability for any injury or damage that may result from your reliance upon the map or any of the information contained on it.

**Orange County Water District**  
**Surface Water Recharge Facilities**  
 Date Prepared: 06/11/2018



- 1933 OCWD established to manage groundwater and seawater intrusion
- 1950 OCWD first purchase of imported water
- 1954 establishes replenishment assessment
- Factory 21 Operational
- 2008 Groundwater Replenishment System operational 70 MGD
- 2015 GWRS 100 MGD (112,000 AFY)
  - 30 MGD to seawater intrusion barrier
  - 70 MGD to recharge basins
- 2023 GWRS 130 MGD
- Recharges approximately 250,000 – 300,000 AFY

# References/Contacts

- International Association of Hydrogeologists - Managed Aquifer Recharge Commission  
<https://recharge.iah.org/>
  - ISMAR10 in Madrid, Spain 20-24 May 2019
- National Ground Water Association [www.ngwa.org](http://www.ngwa.org)
- American Groundwater Trust [www.agwt.org](http://www.agwt.org)
- Groundwater Resources Association of California
  - [www.grac.org](http://www.grac.org) BSMAR17 in Arizona in 2020
- Department of Water Resources Sustainable Groundwater Management Program
  - <https://water.ca.gov/Programs/Groundwater-Management/SGMA-Groundwater-Management>
- Santa Clara Valley Water District
  - <https://www.valleywater.org/your-water/where-your-water-comes-from/groundwater>
  - Vanessa de la Piedra [vdelapiedra@valleywater.org](mailto:vdelapiedra@valleywater.org)
- Regional Water Authority <http://rwah2o.org/> John Woodling [jwoodling@rwah2o.org](mailto:jwoodling@rwah2o.org)
- Kern Water Bank <http://www.kwb.org/> Jon Parker [jparker@kwb.org](mailto:jparker@kwb.org)
- Water Replenishment of Southern California <http://www.wrd.org/>
  - Ted Johnson [tjohnson@wrdd.org](mailto:tjohnson@wrdd.org)
- Orange County Water District [www.ocwd.org](http://www.ocwd.org) Adam Hutchinson [ahutchinson@ocwd.com](mailto:ahutchinson@ocwd.com)

# Questions and Comments

